

Lunar Duo Tent



40 Ounce — 2 Person — Three Season Tent



Setting Up Your Tent:

Choose a tent site away from low hanging branches, and clear site of sharp objects such as sticks or rocks. The Lunar Duo ultralight floor is constructed of 30 Denier silicone coated nylon. Lightweight fabric is more vulnerable to punctures and abrasion than heavier material. Take care to avoid contact with sharp or abrasive objects. To ensure a long life for your floor, we recommend you put down a ground cloth of Tyvek or some other material. You can purchase ground cloths to fit your tent from us.

1. Lay out tent as desired .
2. Insert the two curved spreader bars into the pockets in the interior roof above each door.
3. Insert a stake through each of the four corners.
4. Insert end tip of hiking pole into grommet at the top of one door, and place handle end of pole on ground. Recommended front pole height is **45 inches high**.
5. Pull out front guyline and stake. Adjust guyline tension, and position of pole as needed.
6. Repeat for the second pole.
7. Adjust the tension on the canopy as needed.

Allow a half hour for the tent material to relax then re-adjust tension as needed. Make sure you've got a nice even canopy slope running from front to rear of the tent.

For increased stability in extremely windy conditions, attach guy lines (not included) to each of the side tie-out loops and stake out or tie off to vegetation.

Seam Sealing:

Before using your tent, seal exposed outside seams with a Silicone based seam sealer. If you purchased SilNet™, follow the package instructions. (**Hint:** To control the application better, purchase a plastic glue syringe for about \$1 at any art supply store, and cut off part of the tip to make a larger opening. You will be able to seal the entire tent with 1 tube.) To make your own sealer, follow the note below:

Homemade silicone seam sealer:

To make your own seam sealer, check out our seam sealer page on our website at <http://www.sixmoondesigns.com/support/seam.asp>.

Working in a well ventilated area, pour a small amount into a paper cup, and close the jar to keep rest of sealer from thickening. Use a small brush to apply a thin coat of sealer to all exposed outside seams. Spread seams open flat and hold them taut while applying, to ensure even coverage. If sealer thickens while applying, stir in a few drops of mineral spirits. Use waxed paper to separate overlapping areas of wet sealer.

Hang your tent, or lay it out flat, and cure for at least 12 hours after sealing. Hanging with simple wire hooks on the support brackets of a garage door works well, as does hanging over a shower rod with floor sides together. Once cured, the sealer dries to a clear matte finish that is nearly invisible, and will be both durable and flexible.

Safety Notes:

DO NOT expose tent to open flame from a fire, or stove.

DO NOT cook inside tent.

Price:

Seam Sealing:

Ultralight Floor:

Warranty

The Six Moon Designs gear is designed for a long service life. We have a lifetime warranty on workmanship. Since no gear is completely indestructible our warranty does not cover the following conditions:

- Normal wear and tear associated with usage.
- Damage resulting from abuse.
- Degradation of the materials by long term UV exposure.
- Exhaustion of zippers.
- Alteration of the gear from its original form.

Should you need to return the product for warranty or repair, contact us at **store@sixmoondesigns.com** for a return authorization number. We will inspect the gear to determine if defective. At which time we will either repair or replace free of charge. Service or repair of items not covered under warranty will be done at nominal charge.